Flex Light F2 300mm x 5m brown

Article number: 8021110030

MAGE
Damit Macher machen können.

Product overview

MAGE Flex Light F2 is a highly flexible wall and chimney connection roll made of continuously pleated aluminum composite with a color coating. This combination of sturdy aluminum and flexible plastic offers high break resistance. The prefabricated bending beads allow for bending in both the longitudinal and transverse directions. The entire back is coated with adhesive butyl and covered with a two-part, overlapping protective film, which allows the product to be applied step by step. It offers lasting protection in all weather conditions and, with a stretch factor of 20% in both the longitudinal and transverse directions, achieves optimum conformability to the roofing.



- Visually appealing surface structure
- Targeted formability through bending beads
- QNG certified
- Weather, long-term, and corrosion resistant

Technical specifications

Specifications	
Technical	
Colour	Brown
Colour indication	RAL 8019
Material	ALU/Butyl
Performance	
Temperature resistance (min.)	-40 °C
Temperature resistance (max.)	90 °C
Can be glued	☑
Reinforcement	☒
Self adhesive	☑
Stretch length	20 %
Stretch width	20 %
Dimensions	
Length gross	5 m
Length gross	5,000 mm
Width	300 mm
Height	310 mm
Thickness	2.4 mm
Net weight	2.25 kg

© 2026 Ubbink. All rights reserved.| Content is subject to change without notice. Availability and configurations may differ per country. | UB-22-09-2026-INT-EN

MAGE Roof & Building Components GmbH
An den Steinenden 7 • 04916 Herzberg (Elster) • Tel.: +49 3535 4007-0 • Fax: +49 3535 4007-32
info@mage-roof.com • www.mage-roof.com