# AirTex Top SB grey 1,5 x 50m

Article number: 8031780000

MAGE
Damit Macher machen können.

## Product overview

AirTex Top SB is an energy-efficient, diffusion-open, three-layer underlay membrane.

- CE certified
- As an underlay membrane for particularly flat roofs
- Hot air and cold weldable
- Weldable connection details can be formed
- Tested for driving rain tightness of membrane and seam
- Diffusion open
- Very good tear and nail pull-out resistance
- Non-slip surface with good grip
- Plasticizer-free, PVC-free




## Technical specifications

| Specifications | |
|---|---|
| **Technical** | |
| **Colour** | Grey |
| **Adhesive tape included** | ☑ |
| **Grammature** | 310 g/m² |
| **Number of layers** | 3 |
| **Performance** | |
| **Temperature resistance (min.)** | -40 °C |
| **Temperature resistance (max.)** | 80 °C |
| **Reaction to fire: Euro class** | E |
| **Nail tear strength diagonal** | 200 N |
| **Nail tear strength length** | 150 N |
| **Reinforcement** | ☒ |
| **SD value** | 0.04 M |
| **Stretch length** | 65 % |
| **Stretch after aging length** | 65 % |
| **Stretch width** | 40 % |
| **Stretch after aging width** | 40 % |
| **Tensile strength diagonal** | 230 N |
| **Tensile strength length** | 290 N |
| **Tensile strength diagonal after aging** | 230 N |
| **Tensile strength length after aging** | 290 N |
| **UV resistance** | ☒ |

© 2026 Ubbink. All rights reserved.| Content is subject to change without notice. Availability and configurations may differ per country. | UB-22-09-2026-INT-EN

**MAGE Roof & Building Components GmbH**
An den Steinenden 7 • 04916 Herzberg (Elster) • Tel.: +49 3535 4007-0 • Fax: +49 3535 4007-32
info@mage-roof.com • www.mage-roof.com

# AirTex Top SB grey 1,5 x 50m

Article number: 8031780000

MAGE
Damit Macher machen können.

## Technical specifications (continuation)

| Performance | |
|---|---|
| UV resistance period | 3 Months |
| Water tightness class | W1 |
| **Dimensions** | |
| Length gross | 50 m |
| Length gross | 50,000 mm |
| Width | 1.5 m |
| Width | 1,500 mm |
| Height | 190 mm |
| Thickness | 0.62 mm |
| Net weight | 25.5 kg |
| M2 per roll | 75 |

© 2026 Ubbink. All rights reserved.| Content is subject to change without notice. Availability and configurations may differ per country. | UB-22-09-2026-INT-EN

**MAGE Roof & Building Components GmbH**
An den Steinenden 7 • 04916 Herzberg (Elster) • Tel.: +49 3535 4007-0 • Fax: +49 3535 4007-32
info@mage-roof.com • www.mage-roof.com