# Apron Flashing Zinc 140mm x 18m

Article number: 8026030020

MAGE
Damit Macher machen können.

## Product overview

Highly flexible flashing made of continuously pleated aluminum for folding onto connecting plates and roof windows. A prefabricated bend ensures a clean transition from the sheet metal fold to the flashing without damaging the pleating. The back is coated with two butyl adhesive strips, which serve as an installation aid for folding and for sealing on the roof covering. It offers lasting protection in all weather conditions and, with a longitudinal stretch factor of 30%, achieves optimum conformability to the roof covering.

- Visually appealing surface structure
- Optimal moldability to the roofing
- Additional butyl adhesive strip as a fixing aid in the sheet metal fold
- Weather-resistant, long-lasting, and corrosion-resistant



## Technical specifications

| Specifications | |
|---|---|
| **Technical** | |
| **Colour** | Material own |
| **Material** | Zinc |
| **Performance** | |
| **Temperature resistance (min.)** | -40 °C |
| **Temperature resistance (max.)** | 90 °C |
| **Can be glued** | ☑ |
| **Reinforcement** | ☒ |
| **Self adhesive** | ☑ |
| **Stretch length** | 30 % |
| **Stretch width** | 0 % |
| **Dimensions** | |
| **Length gross** | 18 m |
| **Length gross** | 18,000 mm |
| **Width** | 140 mm |
| **Height** | 285 mm |
| **Thickness** | 3.7 mm |
| **Net weight** | 4.5 kg |

© 2026 Ubbink. All rights reserved.| Content is subject to change without notice. Availability and configurations may differ per country. | UB-22-09-2026-INT-EN

**MAGE Roof & Building Components GmbH**
An den Steinenden 7 • 04916 Herzberg (Elster) • Tel.: +49 3535 4007-0 • Fax: +49 3535 4007-32
info@mage-roof.com • www.mage-roof.com