FireSafe InsideFlex Alu

Article number: 8031560010

MAGE
Damit Macher machen können.

Product overview

FireSafe InsideFlex Alu is a non-combustible, reflective, and high-density vapor barrier membrane.

- Non-combustible (A2-s1,d0)
- Summer heat protection
- High density sd value >2000m
- Easy to install
- Tested sustainable product (EPD)



Technical specifications

Specifications	
Technical	
Colour	Silver
Material	ALU/ E-glass fibers/ PE
Adhesive tape included	☒
Grammature	140 g/m²
Number of layers	1
Performance	
Reaction to fire: Euro class	A2 - s1 d0
Nail tear strength diagonal	150 N
Nail tear strength length	150 N
Reinforcement	☒
SD value	4,000 M
Tensile strength diagonal	950 N
Tensile strength length	950 N
Tensile strength diagonal after aging	950 N
Tensile strength length after aging	950 N
UV resistance	☒
Dimensions	
Length gross	25 m
Length gross	2,500 mm
Width	1 m
Width	1,000 mm

© 2026 Ubbink. All rights reserved.| Content is subject to change without notice. Availability and configurations may differ per country. | UB-22-09-2026-INT-EN

MAGE Roof & Building Components GmbH
An den Steinenden 7 • 04916 Herzberg (Elster) • Tel.: +49 3535 4007-0 • Fax: +49 3535 4007-32
info@mage-roof.com • www.mage-roof.com

FireSafe InsideFlex Alu

Article number: 8031560010

MAGE
Damit Macher machen können.

Technical specifications (continuation)

Dimensions	
Height	360 mm
Thickness	0.16 mm
Net weight	22 kg
M2 per roll	25

© 2026 Ubbink. All rights reserved.| Content is subject to change without notice. Availability and configurations may differ per country. | UB-22-09-2026-INT-EN

MAGE Roof & Building Components GmbH
An den Steinenden 7 • 04916 Herzberg (Elster) • Tel.: +49 3535 4007-0 • Fax: +49 3535 4007-32
info@mage-roof.com • www.mage-roof.com