Roof ladder aluminum stationary red

Article number: 8051510050

MAGE
Damit Macher machen können.

Product overview

The roof ladder, which is permanently attached to the roof, serves as a fully-fledged roof access system in accordance with DIN EN 12951. It can be extended as required using standard connecting brackets.

- Quick and easy installation and corrosion-resistant
- Weather-resistant, durable,
- Affordable alternative to ladder steps
- For roof pitches from 15° to 60°
- Can be used for plain tiles, clay tiles, and concrete roof tiles



Technical specifications

Specifications	
Technical	
Colour	Red
Colour indication	RAL 8004
Material	Steel hot dip galvanized
Installation	
Roof type	Pitch
Type of tile	Universal
Adjustable	☒
Dimensions	
Length gross	2 m
Length gross	2,000 mm
Width	NaN
Width	340 mm
Height	130 mm
Length of the support bracket	NaN
Net weight	5.25 kg

© 2026 Ubbink. All rights reserved.| Content is subject to change without notice. Availability and configurations may differ per country. | UB-22-09-2026-INT-EN

MAGE Roof & Building Components GmbH
An den Steinenden 7 • 04916 Herzberg (Elster) • Tel.: +49 3535 4007-0 • Fax: +49 3535 4007-32
info@mage-roof.com • www.mage-roof.com