AirTex Comband 100 / 20mm

Article number: 8042020020

MAGE
Damit Macher machen können.

Product overview

Compression strips for joints and connections in building construction and on facades.

- Quick and easy to install
- Suitable for use as a decoupling tape
- Sound and heat insulating
- Flame-retardant
- Suitable for indoor and outdoor use



Technical specifications

Specifications	
Technical	
Colour	Anthracite
Material	PU
Material - layer 1	PU
Elastic	☑
Insulated	☒
Double sides	☒
Performance	
Usage	Interior
Adhesive material	Acrylate
Temperature resistance (min.)	-30 °C
Temperature resistance (max.)	90 °C
Limited shelf life	☑
Self adhesive	☑
Tape application	Air tight
UV resistance	☑
Dimensions	
Length gross	8 m
Length gross	8,000 mm
Width	20 mm
Height	20 mm
Thickness	NaN

© 2026 Ubbink. All rights reserved.| Content is subject to change without notice. Availability and configurations may differ per country. | UB-22-09-2026-INT-EN

MAGE Roof & Building Components GmbH
An den Steinenden 7 • 04916 Herzberg (Elster) • Tel.: +49 3535 4007-0 • Fax: +49 3535 4007-32
info@mage-roof.com • www.mage-roof.com

AirTex Comband 100 / 20mm

Article number: 8042020020

MAGE
Damit Macher machen können.

Technical specifications (continuation)

Dimensions	
Net weight	0.286 kg

© 2026 Ubbink. All rights reserved.| Content is subject to change without notice. Availability and configurations may differ per country. | UB-22-09-2026-INT-EN

MAGE Roof & Building Components GmbH
An den Steinenden 7 • 04916 Herzberg (Elster) • Tel.: +49 3535 4007-0 • Fax: +49 3535 4007-32
info@mage-roof.com • www.mage-roof.com