Gutter Inlet Alu 230mm x 5m black

Article number:

MAGE
Damit Macher machen können.

Product overview

MAGE gutter inlet made of continuously pleated aluminium with butyl adhesive strips and bending beads, serving as the eaves-side finish for the sub-roof.

- Quick and easy installation
- Weather-resistant and durable
- Easy to fold thanks to the folding beads
- Integrated butyl adhesive strip for additional rain protection and to secure the underlay
- ZVDH-guaranteed & QNG-certified



Technical specifications

Specifications	
Technical	
Colour	Material own
Material	ALU/Butyl
Performance	
Temperature resistance (min.)	-40 °C
Temperature resistance (max.)	90 °C
Can be glued	☑
Reinforcement	☒
Self adhesive	☑
Stretch length	30 %
Stretch width	0 %
Dimensions	
Length gross	5 m
Length gross	5,000 mm
Width	230 mm
Height	230 mm
Thickness	2 mm
Net weight	1.45 kg

© 2026 Ubbink. All rights reserved.| Content is subject to change without notice. Availability and configurations may differ per country. | UB-22-09-2026-INT-EN

MAGE Roof & Building Components GmbH
An den Steinenden 7 • 04916 Herzberg (Elster) • Tel.: +49 3535 4007-0 • Fax: +49 3535 4007-32
info@mage-roof.com • www.mage-roof.com