FireSafe W1 Alu

Article number: 8031750020

MAGE
Damit Macher machen können.

Product overview

FireSafe W1 Alu is a reflective, highly diffusion-open, and non-combustible underlay and roof membrane with self-adhesive strips for roofs and facades.

- Non-combustible (A2-s1,d0)
- With self-adhesive strip
- UV-stable
- Summer heat protection
- Highly diffusion-open sd value 0.08 m
- Tested sustainable product (EPD)



Technical specifications

Specifications	
Technical	
Colour	Silver
Material	ALU/ E-glass fibers/ PE
Adhesive tape included	☑
Grammature	430 g/m²
Number of layers	1
Performance	
Temperature resistance (min.)	-36 °C
Temperature resistance (max.)	90 °C
Nail tear strength diagonal	450 N
Nail tear strength length	580 N
Reinforcement	☒
SD value	0.08 M
Stretch length	6 %
Stretch after aging length	6 %
Stretch width	5 %
Stretch after aging width	5 %
Tensile strength diagonal	3200 N
Tensile strength length	3000 N
Tensile strength diagonal after aging	3200 N
Tensile strength length after aging	3000 N
UV resistance	☒

© 2026 Ubbink. All rights reserved.| Content is subject to change without notice. Availability and configurations may differ per country. | UB-22-09-2026-INT-EN

MAGE Roof & Building Components GmbH
An den Steinenden 7 • 04916 Herzberg (Elster) • Tel.: +49 3535 4007-0 • Fax: +49 3535 4007-32
info@mage-roof.com • www.mage-roof.com

FireSafe W1 Alu

Article number: 8031750020

MAGE
Damit Macher machen können.

Technical specifications (continuation)

Performance	
UV resistance period	9 Months
Water tightness class	W1
Dimensions	
Length gross	35 m
Length gross	35,000 mm
Width	1.2 m
Width	1,200 mm
Height	180 mm
Thickness	0.48 mm
Net weight	18 kg
M2 per roll	42

© 2026 Ubbink. All rights reserved.| Content is subject to change without notice. Availability and configurations may differ per country. | UB-22-09-2026-INT-EN

MAGE Roof & Building Components GmbH
An den Steinenden 7 • 04916 Herzberg (Elster) • Tel.: +49 3535 4007-0 • Fax: +49 3535 4007-32
info@mage-roof.com • www.mage-roof.com